

SPECIFICATIONS

CEILING CONCEALED HEAT PUMP MODELS - R 407C

MODEL		INDOOR UNIT	MCC 010CR	MCC 015CR	MCC 020CR	MCC 025CR	
		OUTDOOR UNIT	M4LC 010BR	M4LC 015BR	M4LC 020BR	M4LC 025BR	
NOMINAL COOLING CAPACITY		kcal/h	2 268	2 772	4 536	5 170	
		W	2 637	3 223	5 274	6 008	
		Btu/h	9 000	11 000	18 000	20 500	
NOMINAL HEATING CAPACITY		kcal/h	2 394	3 150	4 790	6 050	
		W	2 784	3 663	5 569	7 034	
		Btu/h	9 500	12 500	19 000	24 000	
POWER SOURCE		V/Ph/Hz	220 - 240 / 1 / 50				
REFRIGERANT / CONTROL			R407C / CAPILLARY TUBE IN OUTDOOR				
FAN	AIR FLOW	cfm/cmm	300 / 8.50	430 / 12.2	620 / 17.0	840 / 23.8	
	STATIC PRESSURE	mm Aq	5	5	5	5	
	FAN MOTOR		4 POLES x 22W	4 POLES x 30W	4 POLES x 55W	4 POLES x 100W	
	RATED INPUT POWER	W	71	102	148	180	
	RATED RUNNING CURRENT	A	0,30	0,43	0,65	0,77	
COIL	TUBE	MATERIAL	SEAMLESS COPPER				
		DIAMETER	9.52 / 3/8				
		THICKNESS	0.35 / 0.014				
	FIN	MATERIAL	ALUMINIUM				
		THICKNESS	0.11 / 0.0043				
		ROW	3	3	3	3	
	FIN PER INCH	12	14	12	12		
FACE AREA	m ² /ft ²	0.115 / 1.238	0.143 / 1.542	0.176 / 1.892	0.203 / 2.187		
DIMENSION	HEIGHT	mm/in	261 / 10.28	261 / 10.28	261 / 10.28	261 / 10.28	
	WIDTH	mm/in	765 / 30.12	905 / 35.63	1,065 / 41.93	1,200 / 47.24	
	DEPTH	mm/in	411 / 16.18	411 / 16.18	411 / 16.18	411 / 16.18	
WEIGHT	kg	17	21	22	25		
SOUND PRESSURE LEVEL	dBa	39 / 37 / 33	41 / 38 / 33	44 / 43 / 40	46 / 44 / 41		
CONTROL	ROOM TEMPERATURE OPERATION		MICROCOMPUTER CONTROLLED THERMOSTAT SLM WIRED HANDSET (OPTIONAL AC5300 REMOTE CONTROLLER)				
CONDENSATE DRAIN SIZE	mm/in	19.05 / 3/4					
AIR FILTER		WASHABLE SARAN NET (OPTIONAL)					
PACKING DIMENSION	HEIGHT	mm/in	410 / 16.14	410 / 16.14	410 / 16.14	410 / 16.14	
	WIDTH	mm/in	951 / 37.44	1,091 / 42.95	1,251 / 49.25	1,386 / 54.57	
	DEPTH	mm/in	535 / 21.06	535 / 21.06	535 / 21.06	535 / 21.06	
POWER SOURCE	V/Ph/Hz	220 - 240 / 1 / 50		220 - 240 / 1 / 50 / < 380 - 415 / 3 / 50 >			
COMP.	COMPRESSOR TYPE		ROTARY HERMETIC				
	CAPACITOR	µF	30	30	45 / < NIL >	50 / < NIL >	
	LOCK ROTOR AMP.	A	18	29	54 / < 21 >	58 / < 26 >	
	RATED RUNNING CURRENT (COOLING)	A	4,00	6,20	9,50 / < 3.6 >	12,60 / < 4.8 >	
	RATED RUNNING CURRENT (HEATING)	A	3,30	5,70	10,10 / < 3.5 >	12,50 / < 4.5 >	
	RATED INPUT POWER (COOLING)	W	900	1 350	2,002 / < 1,893 >	2,571 / < 2,508 >	
	RATED INPUT POWER (HEATING)	W	750	1 200	2,096 / < 1,850 >	2,549 / < 2,400 >	
	PROTECTION DEVICE		OVERLOAD PROTECTION				
	FAN TYPE / DRIVE		PROPELLER / DIRECT				
	BLADE MATERIAL		GLASS REINFORCED ACRYL STYRENE RESIN				
FAN	DIAMETER	mm/in	355 / 14.0		420 / 16.5		
	RATED RUNNING CURRENT	A	0,28		0,56		
	RATED OUTPUT POWER	W	30		55		
	RATED INPUT POWER	W	62		133		
COIL	TUBE	MATERIAL	S.I.G.C	S.I.G.C	S.B.C.	S.I.G.C	
		DIAMETER	9.52 / 3/8				
		THICKNESS	0.35 / 0.014			0.36 / 0.014 AVERAGE	
	FIN	MATERIAL	ALUMINIUM				
		THICKNESS	0.127 / 0.005				
		ROW	1	1	2	2	
	FIN PER INCH	19	19	14	14		
FACE AREA	m ² /ft ²	0.32 / 3.5		0.51 / 5.53			
DIMENSION	HEIGHT	mm/in	494 / 19.4		646 / 25.4		
	WIDTH	mm/in	740 / 29.1		840 / 33.1		
	DEPTH	mm/in	270 / 10.6		330 / 13.0		
WEIGHT	kg	31	34	57	58		
CASING	MATERIAL	GALVANISED MILD STEEL					
	THICKNESS	mm/in	0.8 / 0.031				
	FINISHING	POLYESTER POWDER					
SOUND PRESSURE LEVEL	dBa	48	49	52	53		
PIPE	TYPE		FLARE VALVE				
		SIZE	LIQUID	mm/in	6.35 / 1/4	6.35 / 1/4	6.35 / 1/4
		GAS	mm/in	9.52 / 3/8	12.70 / 1/2	15.88 / 5/8	15.88 / 5/8
PACKING DIMENSION	HEIGHT	mm/in	558 / 22.0		710 / 28.0		
	WIDTH	mm/in	851 / 33.5		957 / 37.7		
	DEPTH	mm/in	401 / 15.8		461 / 18.1		

- 1) ALL SPECIFICATIONS ARE SUBJECTED TO CHANGE BY THE MANUFACTURER WITHOUT PRIOR NOTICE.
- 2) ALL UNITS ARE BEING TESTED AND COMPLY TO ARI 210/240-89
- 3) NOMINAL COOLING AND HEATING CAPACITY ARE BASED ON THE CONDITIONS BELOW :
 - a) COOLING - 26.7°C DB / 19.4°C WB INDOOR AND 35°C DB OUTDOOR
 - b) HEATING - 21.1°C DB / 15.6°C WB INDOOR AND 8.3°C DB / 6.1°C WB OUTDOOR
- 4) ALLOWABLE OPERATING RANGE
 - a) COOLING - 19.4°C DB / 13.9°C WB INDOOR AND 19.4°C DB OUTDOOR TO 26.7°C DB / 19.4°C WB INDOOR AND 46.1°C DB OUTDOOR
 - b) HEATING - 21.0°C DB INDOOR AND -8.3°C DB / -9.4°C WB OUTDOOR TO 26.7°C DB INDOOR AND 23.9°C DB / 18.3°C WB

Abbreviation

S.B.C. - SEAMLESS BARE COPPER
S.I.G.C - SEAMLESS INNER GROOVE COPPER

SPECIFICATIONS

CEILING CONCEALED COOLING ONLY MODELS

MODEL		INDOOR UNIT		MCC 030CR	MCC 040CR	MCC 050CR
		OUTDOOR UNIT		M4LC 030CR	M4LC 040CR	M4LC 050CR
NOMINAL COOLING CAPACITY		kcal/h		7 310	9 830	12 100
		W		8 499	11 430	14 068
		Btu/h		29 000	39 000	48 000
NOMINAL HEATING CAPACITY		kcal/h		7 812	10 332	12 600
		W		9 083	12 013	14 654
		Btu/h		31 000	41 000	50 000
POWER SOURCE		V/Ph/Hz		220 - 240 / 1 / 50		
REFRIGERANT / CONTROL				R407C / TXV (OUTDOOR)		
FAN	AIR FLOW	cfm/cmm		900 / 25.49	1,200 / 33.99	1,500 / 42.49
	STATIC PRESSURE	mm Aq		15 / 10 / 5		
	FAN MOTOR	4 POLES				
	RATED INPUT POWER	W		421	550	670
	RATED RUNNING CURRENT	A		1,9	2,6	2,9
COIL	TUBE	MATERIAL	SEAMLESS BARE COPPER			
		DIAMETER	mm/in	9.52 / 3/8		
		THICKNESS	mm/in	0.35 / 0.014		
	FIN	MATERIAL	ALUMINIUM			
		THICKNESS	mm/in	0.127 / 0.005		
		ROW		3	3	3
	FIN PER INCH		12	14	14	
	FACE AREA	m ² /ft ²	0.27 / 2.98	0.31 / 3.44	0.40 / 4.40	
DIMENSION	HEIGHT	mm/in	378 / 14.88			
	WIDTH	mm/in	929 / 36.57	1045 / 41.14	1299 / 51.14	
	DEPTH	mm/in	474 / 18.66			
WEIGHT	kg		39	42	54	
SOUND PRESSURE LEVEL	dB(A)		61 / 59 / 57	61 / 59 / 58	62 / 61 / 60	
CONTROL	ROOM TEMPERATURE OPERATION	MICROCOMPUTER CONTROLLED THERMOSTAT				
		SLM WIRED HANDSET (OPTIONAL AC5300 REMOTE CONTROLLER)				
CONDENSATE DRAIN SIZE	mm/in	19.05 / 3/4				
AIR FILTER	WASHABLE SARAN NET					
PACKING DIMENSION	HEIGHT	mm/in	399 / 15.71			
	WIDTH	mm/in	1110 / 43.70	1229 / 48.39	1481 / 58.31	
	DEPTH	mm/in	615 / 24.21			
POWER SOURCE		V/Ph/Hz		220-240/1/50 / < 380-415/3/50 >	380 - 415 / 3 / 50	
COMPRESSOR TYPE		SCROLL				
CAPACITOR	µF		50 / < NIL >	-	-	
LOCK ROTOR AMP.	A		78 / < 40 >	45	62	
RATED RUNNING CURRENT (COOLING)	A		11.5 / < 4.3 >	6.2	8.8	
RATED RUNNING CURRENT (HEATING)	A		11.4 / < 4.2 >	5.9	7.8	
RATED INPUT POWER (COOLING)	W		2,424 / < 2,414 >	3 565	4 615	
RATED INPUT POWER (HEATING)	W		2,407 / < 2,388 >	3 280	3 734	
PROTECTION DEVICE	OVERLOAD PROTECTION / HI PRESSURE SWITCH					
POWER SOURCE		V/Ph/Hz		220 - 240 / 1 / 50		
FAN TYPE / DRIVE		PROPELLER / DIRECT				
BLADE MATERIAL		GLASS REINFORCED ACRYL STYRENE RESIN				
DIAMETER	mm/in	610 / 24				
RATED RUNNING CURRENT	A	1,09				
RATED OUTPUT POWER	W	145				
RATED INPUT POWER	W	241				
COIL	TUBE	MATERIAL	S.B.C.			
		DIAMETER	mm/in	9.52 / 3/8		
		THICKNESS	mm/in	0.35 / 0.014		
	FIN	MATERIAL	ALUMINIUM (CORRUGATED)			
		THICKNESS	mm/in	0.127 / 0.005		
		ROW		1	2	2
	FIN PER INCH		16	14	16	
	FACE AREA	m ² /ft ²	0.87 / 9.33			
DIMENSION	HEIGHT	mm/in	850 / 33.46			
	WIDTH	mm/in	1,030 / 40.55			
	DEPTH	mm/in	400 / 15.75			
WEIGHT	kg		95	100	105	
CASING	MATERIAL	ELECTRO-GALVANISED MILD STEEL				
	THICKNESS	mm/in	0.8 / 0.031			
	FINISHING	POLYESTER POWDER				
SOUND PRESSURE LEVEL	dB(A)		60	59	62	
PIPE	TYPE	FLARE VALVE				
		SIZE		9.52 / 3/8		
		LIQUID	mm/in	9.52 / 3/8	9.52 / 3/8	9.52 / 3/8
	GAS	mm/in	15.88 / 5/8	19.05 / 3/4	19.05 / 3/4	
PACKING DIMENSION	HEIGHT	mm/in	1,000 / 39.37			
	WIDTH	mm/in	1,200 / 47.24			
	DEPTH	mm/in	560 / 22.05			

- 1) ALL SPECIFICATIONS ARE SUBJECTED TO CHANGE BY THE MANUFACTURER WITHOUT PRIOR NOTICE.
- 2) ALL UNITS ARE BEING TESTED AND COMPLY TO ARI 210/240-89
- 3) NOMINAL COOLING AND HEATING CAPACITY ARE BASED ON THE CONDITIONS BELOW :
 - a) COOLING - 26.7°C DB / 19.4°C WB INDOOR AND 35°C DB OUTDOOR
 - b) HEATING - 21.1°C DB / 15.6°C WB INDOOR AND 8.3°C DB / 6.1°C WB OUTDOOR
- 4) ALLOWABLE OPERATING RANGE
 - a) COOLING - 19.4°C DB / 13.9°C WB INDOOR AND 19.4°C DB OUTDOOR TO 26.7°C DB / 19.4°C WB INDOOR AND 46.1°C DB OUTDOOR
 - b) HEATING - 21.0°C DB INDOOR AND -8.3°C DB / -9.4°C WB OUTDOOR TO 26.7°C DB INDOOR AND 23.9°C DB / 18.3°C WB

Abbreviation

S.B.C. - SEAMLESS BARE COPPER
S.I.G.C. - SEAMLESS INNER GROOVE COPPER

SPECIFICATIONS

CEILING CONCEALED COOLING ONLY MODELS

MODEL	INDOOR UNIT		MCC 010C	MCC 015C	MCC 020C	MCC 025C
	OUTDOOR UNIT		M4LC 010B	M4LC 015B	M4LC 020B	M4LC 025B
NOMINAL COOLING CAPACITY		kcal/h	2 268	2 772	4 612	5 292
		W	2 637	3 223	5 363	6 155
		Btu/h	9 000	11 000	18 300	21 000
POWER SOURCE		V/Ph/Hz	220 - 240 / 1 / 50			
REFRIGERANT / CONTROL			R407C / CAPILLARY TUBE IN OUTDOOR			
FAN	AIR FLOW	cfm/cmm	300 / 8.50	430 / 12.2	620 / 17.0	840 / 23.8
	STATIC PRESSURE	mm Aq	5	5	5	5
	FAN MOTOR		4 POLES x 22W	4 POLES x 30W	4 POLES x 55W	4 POLES x 100W
	RATED INPUT POWER	W	71	102	148	180
	RATED RUNNING CURRENT	A	0,30	0,43	0,65	0,77
COIL	TUBE	MATERIAL	SEAMLESS COPPER			
		DIAMETER	mm/in 9.52 / 3/8			
		THICKNESS	mm/in 0.35 / 0.014			
	FIN	MATERIAL	ALUMINIUM			
		THICKNESS	mm/in 0.11 / 0.0043			
		ROW	3	3	3	3
	FIN PER INCH	12	14	12	12	
FACE AREA	m ² /ft ²	0.115 / 1.238	0.143 / 1.542	0.176 / 1.892	0.203 / 2.187	
DIMENSION	HEIGHT	mm/in	261 / 10.28	261 / 10.28	261 / 10.28	261 / 10.28
	WIDTH	mm/in	765 / 30.12	905 / 35.63	1,065 / 41.93	1,200 / 47.24
	DEPTH	mm/in	411 / 16.18	411 / 16.18	411 / 16.18	411 / 16.18
WEIGHT	kg	17	21	22	25	
SOUND PRESSURE LEVEL	dBa	39 / 37 / 33	41 / 38 / 33	44 / 43 / 40	46 / 44 / 41	
CONTROL	ROOM TEMPERATURE OPERATION		MICROCOMPUTER CONTROLLED THERMOSTAT			
			SLM WIRED HANDSET (OPTIONAL AC5300 REMOTE CONTROLLER)			
CONDENSATE DRAIN SIZE	mm/in	19.05 / 3/4				
AIR FILTER		WASHABLE SARAN NET (OPTIONAL)				
PACKING DIMENSION	HEIGHT	mm/in	410 / 16.14	410 / 16.14	410 / 16.14	410 / 16.14
	WIDTH	mm/in	951 / 37.44	1,091 / 42.95	1,251 / 49.25	1,386 / 54.57
	DEPTH	mm/in	535 / 21.06	535 / 21.06	535 / 21.06	535 / 21.06
POWER SOURCE		V/Ph/Hz	220 - 240 / 1 / 50 / < 380 - 415 / 3 / 50 >			
COMPRESSOR	COMPRESSOR TYPE		ROTARY HERMETIC			
	CAPACITOR	µF	30	30	45 / < NIL >	50 / < NIL >
	LOCK ROTOR AMP.	A	18	29	54 / < 21 >	58 / < 26 >
	RATED RUNNING CURRENT	A	4,00	6,20	9.91 / < 3.6 >	12.50 / < 4.8 >
	RATED INPUT POWER	W	900	1 350	2,112 / < 1,893 >	2,660 / < 2,508 >
PROTECTION DEVICE		OVERLOAD PROTECTION				
FAN	FAN TYPE / DRIVE		PROPELLER / DIRECT			
	BLADE MATERIAL		GLASS REINFORCED ACRYL STYRENE RESIN			
	DIAMETER	mm/in	355 / 14.0		420 / 16.5	
	RATED RUNNING CURRENT	A	0,2	0,28	0,56	
	RATED OUTPUT POWER	W	20	30	55	
RATED INPUT POWER	W	50	62	133		
COIL	TUBE	MATERIAL	S.I.G.C	S.I.G.C	S.B.C.	S.I.G.C
		DIAMETER	mm/in 9.52 / 3/8			
		THICKNESS	mm/in 0.35 / 0.014			0.36 / 0.014 AVERAGE
	FIN	MATERIAL	ALUMINIUM (SLIT TYPE)			
		THICKNESS	mm/in 0.127 / 0.005			
		ROW	1	1	2	2
	FIN PER INCH	18	19	14	14	
FACE AREA	m ² /ft ²	0.32 / 3.5		0.51 / 5.53		
DIMENSION	HEIGHT	mm/in	494 / 19.4		646 / 25.4	
	WIDTH	mm/in	740 / 29.1		840 / 33.1	
	DEPTH	mm/in	270 / 10.6		330 / 13.0	
WEIGHT	kg	31	34	57	58	
CASING	MATERIAL	GALVANISED MILD STEEL				
	THICKNESS	mm/in	0.8 / 0.031			
	FINISHING	POLYESTER POWDER				
SOUND PRESSURE LEVEL	dBa	48	49	52	53	
PIPE	TYPE	FLARE VALVE				
	SIZE	LIQUID	mm/in 6.35 / 1/4	6.35 / 1/4	6.35 / 1/4	9.52 / 3/8
		GAS	mm/in 9.52 / 3/8	12.70 / 1/2	15.88 / 5/8	15.88 / 5/8
PACKING DIMENSION	HEIGHT	mm/in	558 / 22.0		710 / 28.0	
	WIDTH	mm/in	851 / 33.5		957 / 37.7	
	DEPTH	mm/in	401 / 15.8		461 / 18.1	

1) ALL SPECIFICATIONS ARE SUBJECTED TO CHANGE BY THE MANUFACTURER WITHOUT PRIOR NOTICE.

2) ALL UNITS ARE BEING TESTED AND COMPLY TO ARI 210/240-89

3) NOMINAL COOLING CAPACITY IS BASED ON THE CONDITIONS BELOW :

a) COOLING - 26.7°C DB / 19.4°C WB INDOOR AND 35°C DB OUTDOOR

4) ALLOWABLE OPERATING RANGE

a) COOLING - 19.4°C DB / 13.9°C WB INDOOR AND 19.4°C DB OUTDOOR TO

26.7°C DB / 19.4°C WB INDOOR AND 46.1°C DB OUTDOOR

Abbreviation

S.B.C. - SEAMLESS BARE COPPER

S.I.G.C- SEAMLESS INNER GROOVE COPPER

SPECIFICATIONS

CEILING CONCEALED COOLING ONLY MODELS

MODEL		INDOOR UNIT	MCC 030C	MCC 040C	MCC 050C	MCC 060C	
		OUTDOOR UNIT	M4LC 030C	M4LC 040C	M4LC 050C	M4LC 060C	
NOMINAL COOLING CAPACITY	kcal/h		7 560	9 576	12 600	13 860	
	W		8 790	11 134	14 650	16 120	
	Btu/h		30 000	38 000	50 000	55 000	
POWER SOURCE		V/Ph/Hz	220 - 240 / 1 / 50				
REFRIGERANT / CONTROL			R407C / CAPILLARY TUBE (INDOOR)				
FAN	AIR FLOW	cfm/cmm	900 / 25.49	1,200 / 33.99	1,500 / 42.49	1,800 / 50.99	
	STATIC PRESSURE	mm Aq	15 / 10 / 5				
	FAN MOTOR		4 POLES				
	RATED INPUT POWER	W	421	550	670	748	
	RATED RUNNING CURRENT	A	1,9	2,6	2,9	3,2	
COIL	TUBE	MATERIAL	SEAMLESS BARE COPPER				
		DIAMETER	9.52 / 3/8				
		THICKNESS	0.35 / 0.014				
	FIN	MATERIAL	ALUMINIUM				
		THICKNESS	mm/in	0.127 / 0.005			
		ROW		3	3	3	3
		FIN PER INCH		12	14	14	14
		FACE AREA	m ² /ft ²	0.27 / 2.98	0.31 / 3.44	0.40 / 4.40	0.47 / 5.16
DIMENSION	HEIGHT	mm/in	378 / 14.88				
	WIDTH	mm/in	929 / 36.57	1045 / 41.14	1299 / 51.14	1499 / 59.02	
	DEPTH	mm/in	474 / 18.66				
WEIGHT	kg	39	42	54	62		
	SOUND PRESSURE LEVEL	dBA	61 / 59 / 57	61 / 59 / 58	62 / 61 / 60	62 / 61 / 60	
CONTROL		ROOM TEMPERATURE OPERATION	MICROCOMPUTER CONTROLLED THERMOSTAT				
			SLM WIRED HANDSET (OPTIONAL AC5300 REMOTE CONTROLLER)				
CONDENSATE DRAIN SIZE		mm/in	19.05 / 3/4				
AIR FILTER			WASHABLE SARAN NET				
PACKING DIMENSION	HEIGHT	mm/in	399 / 15.71				
	WIDTH	mm/in	1110 / 43.70	1229 / 48.39	1481 / 58.31	1685 / 66.34	
	DEPTH	mm/in	615 / 24.21				
OUTDOOR UNIT	POWER SOURCE		V/Ph/Hz	220-240/1/50 / < 380-415/3/50 >	380 - 415 / 3 / 50		
	COMPRESSOR TYPE			SCROLL			
	CAPACITOR		µF	50 / < NIL >	NIL	NIL	NIL
	LOCK ROTOR AMP.		A	78 / < 40 >	45	62	74
	RATED RUNNING CURRENT		A	11.4 / < 4.5 >	6,3	8,2	8,4
	RATED INPUT POWER		W	2,560 / < 2,550 >	3 741	4 328	4 859
	PROTECTION DEVICE			OVERLOAD PROTECTION / HI-LO PRESSURE SWITCH			
	POWER SOURCE		V/Ph/Hz	220 - 240 / 1 / 50			
	FAN TYPE / DRIVE			PROPELLER / DIRECT			
	BLADE MATERIAL			GLASS REINFORCED ACRYL STYRENE RESIN			
FAN	DIAMETER		mm/in	610 / 24			
	RATED RUNNING CURRENT		A	1,09		2,3	
	RATED OUTPUT POWER		W	145		400	
	RATED INPUT POWER		W	241		655	
COIL	TUBE	MATERIAL	S.B.C.				
		DIAMETER	9.52 / 3/8				
		THICKNESS	0.35 / 0.014				
	FIN	MATERIAL	ALUMINIUM (CORRUGATED)				
		THICKNESS	mm/in	0.127 / 0.005			
		ROW		1	2	2	2
	FIN PER INCH		16	14	16	16	
	FACE AREA	m ² /ft ²	0.87 / 9.33				
DIMENSION	HEIGHT	mm/in	850 / 33.46				
	WIDTH	mm/in	1,030 / 40.55				
	DEPTH	mm/in	400 / 15.75				
WEIGHT	kg	95	100	105	105		
CASING	MATERIAL		ELECTRO-GALVANISED MILD STEEL				
	THICKNESS		mm/in	0.8 / 0.031			
	FINISHING			POLYESTER POWDER			
SOUND PRESSURE LEVEL		dBA	60	59	62	71	
PIPE	TYPE		FLARE VALVE				
	SIZE	LIQUID	mm/in	9.52 / 3/8	9.52 / 3/8	9.52 / 3/8	12.7 / 1/2
		GAS	mm/in	15.88 / 5/8	19.05 / 3/4	19.05 / 3/4	19.05 / 3/4
PACKING DIMENSION	HEIGHT	mm/in	1,000 / 39.37				
	WIDTH	mm/in	1,200 / 47.24				
	DEPTH	mm/in	560 / 22.05				

1) ALL SPECIFICATIONS ARE SUBJECTED TO CHANGE BY THE MANUFACTURER WITHOUT PRIOR NOTICE.

2) ALL UNITS ARE BEING TESTED AND COMPLY TO ARI 210/240-89

3) NOMINAL COOLING CAPACITY IS BASED ON THE CONDITIONS BELOW :

a) COOLING - 26.7°C DB / 19.4°C WB INDOOR AND 35°C DB OUTDOOR

4) ALLOWABLE OPERATING RANGE

a) COOLING - 19.4°C DB / 13.9°C WB INDOOR AND 19.4°C DB OUTDOOR TO 26.7°C DB / 19.4°C WB INDOOR AND 46.1°C DB OUTDOOR

Abbreviation

S.B.C. - SEAMLESS BARE COPPER

S.I.G.C.- SEAMLESS INNER GROOVE COPPER